




Inset

halogène tension réseau




Facette 50 40W-230V-E14





| m | 25° | lx |
|---|------|-----|
| 1 | 0,44 | 950 |
| 2 | 0,88 | 237 |
| 3 | 1,32 | 105 |
| 4 | 1,76 | 60 |

Réflecteur Ø50 40W-E14 40W = 400 lm



Inset 50

| Code | Couleur | Ø d'encastrement (mm) | Hauteur (mm) |
|---------|---------|-----------------------|--------------|
| 3085400 | Blanc | 72 | 120 |





Halogène ES63 75W-GU10-25°




| m | 25° | lx |
|---|-----|------|
| 1 | 0,4 | 2251 |
| 2 | 0,9 | 637 |
| 3 | 1,3 | 284 |
| 4 | 1,8 | 159 |

Inset ES63 Orientable livré avec lampe halogène ES63 75W 230V 25°

| Code | Couleur | Ø d'encastrement (mm) | Hauteur (mm) | Hauteur d'encastrement (mm) |
|---------|---------|-----------------------|--------------|-----------------------------|
| 3086050 | Blanc | 82 | 80 | 110 |
| 3086070 | Argent | 82 | 80 | 110 |



Halogène ES63 75W-GU10-25°



| m | 25° | lx |
|---|-----|------|
| 1 | 0,4 | 2251 |
| 2 | 0,9 | 637 |
| 3 | 1,3 | 284 |
| 4 | 1,8 | 159 |

Inset ES63 livré avec lampe halogène ES63 75W 230V 25°

| Code | Couleur | Ø d'encastrement (mm) | Hauteur (mm) | Hauteur d'encastrement (mm) |
|---------|---------|-----------------------|--------------|-----------------------------|
| 3085140 | Blanc | 82 | 90 | 120 |