

PRODUCT-DETAILS

OTDC32FT4 OTDC32FT4 DC Switch-disconnector



General Information	
Extended Product Type	OTDC32FT4
Product ID	1SCA123847R1001
EAN	6417019545660
Catalog Description	OTDC32FT4 DC Switch-disconnector
Long Description	OTDC32FT4 DC Switch-disconnector, Terminal bolt kit included, Handle and shaft need to be ordered separately, Door mounting, IEC 660 VDC 32 A double circuit, IEC 1000 VDC 20 A double circuit
Ordering Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Popular Downloads	
Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301079M0206
Mechanical Drawings	OTDC16-32FT4_palikkamalli.igs 1SCC307019F0002 1SCC307020F0002

Screw Terminals

1.2...1.4 N·m

Terminal Type

Tightening Torque

Dimensions	
Product Frame Size	X
Product Net Width	52.5 mn 2.1 ir
Product Net Height	69 mm 2.7 ir
Product Net Depth / Length	87 mn 3.4 ir
Product Net Weight	0.2 kg 0.5 lt
Technical	
Rated Operational Current DC-21B (I _e)	(660 V) 32 A (1000 V) 20 A
Conventional Free-air Thermal Current (I _{th})	45 <i>A</i>
Conventional Thermal Current (I _{the})	Fully Enclosed 45 A
Rated Impulse Withstand Voltage (U _{imp})	8 k\
Rated Insulation Voltage (U_i)	1000 \
Rated Operational Voltage	1000 \
Rated Short-Circuit Making Capacity (I _{cm})	(1000 V DC) 0.8 kA
Rated Short-time Withstand Current (I _{cw})	(1000 V DC) 0.8 kA for 1 s 0.8 kA
Power Loss	at Rated Operating Conditions per Pole 0.5 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Shaft Diameter	6 mm 0.24 ir
Switches Operating Mechanism	Mechanism on Top of the Switch
Position of Line Terminals	Top In - Bottom Ou Bottom In - Top Ou
Operating Mode	Front Operated
Standards	IEC 60947-1, -3
Special Functions	No
Mounting Type	Door mounting
Number of Circuits	2
Number of Poles	
Cable Cross-Section	2.5 16 mm
Degree of Protection	Front IP20

Environmental	
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	NA

Certificates and Declarations (Document Number)		
CCC Certificate	CCC OTDC16-32.pdf	
Declaration of Conformity - CE	1SCC301192D2704	
DNV GL Certificate	1SCC301231D0201	
Environmental Information	NA	
Instructions and Manuals	1SCC301079M0206	
RoHS Information	1SCC301207D0203	

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	90 mm
	3.5 in
Package Level 1 Depth /	54 mm
Length	2.1 in
Package Level 1 Height	90 mm
	3.5 in
Package Level 1 Gross	0.3 kg
Weight	0.6 lb
Package Level 1 EAN	6417019545660

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

OTDC32FT4 4

