

PRODUCT-DETAILS

ZLBM1-3P-M12

ZLBM1-3P-M12 Fuse switch disconnecter



General Information

Extended Product Type	ZLBM1-3P-M12
Product ID	1SEP620011R3000
EAN	7025840088233
Catalog Description	ZLBM1-3P-M12 Fuse switch disconnecter
Long Description	ZLBM1-3P-M12 Fuse switch disconnecter

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical Information	1SEC312023D0201
-----------------------------------	-----------------

Dimensions

Product Frame Size	Low
Product Net Width	99 mm
Product Net Height	662 mm
Product Net Depth / Length	185 mm

Product Net Weight

3.63 kg

Technical

Rated Operational Current AC-21B (I _e)	(690 V) 250 A
Rated Operational Current AC-22B (I _e)	(500 V) 250 A (800 V) 200 A
Rated Operational Current AC-23B (I _e)	(400V) 250 A
Rated Impulse Withstand Voltage (U _{imp})	Main Circuit 8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	Main Circuit 690 V AC
Handle Type	3P
Distance Between Phases	185 mm
Fuse Size	1
Fuse System	DIN
Standards	IEC60947-3
Number of Poles	3
Degree of Protection	Front IP30
Terminal Type	Bolt

Container Information

Package Level 1 Units	shrink-wrap 1 piece
Package Level 1 EAN	7025840088233

Classifications

ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Inline II

Low Voltage Products and Systems → Industries → Solar power → 800V AC

