

PRODUCT-DETAILS

S803U-K30

S803U-K30 High Performance MCB



General Information

Extended Product Type	S803U-K30
Product ID	2CCS863017R0527
EAN	7612271214180
Catalog Description	S803U-K30 High Performance MCB
Long Description	S803U-K30 3 Pole K Characteristic 30A 50kA 240/415VAC High Performance Circuit Breaker HPCB

Technical

Standards	IEC/EN 60947-2 UL 489
Number of Poles	3
Number of Protected Poles	3
Tripping Characteristic	K
Rated Current (I_n)	30
Rated Operational Voltage	240 V AC
Power Loss	2.8 W at Rated Operating Conditions per Pole 0.93 W
Rated Insulation Voltage (U_i)	690 V
Rated Short-Circuit Capacity (I_{cn})	(400 V) 40 kA (230 V) 40 kA
Rated Ultimate Short-Circuit Breaking	(415 V AC) 50 kA

Capacity (I _{cu})	(415 V AC) 40 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	2
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Actuator Marking	I / O
Contact Position Indication	ON / OFF / TRIP
Degree of Protection	IP20
Connecting Capacity	Rigid 0 ... 50 mm ² Flexible 0 ... 70 mm ²
Built-In Depth (t ₂)	82.5 mm

Environmental

Ambient Air Temperature	Operation -25...60 °C
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 50 kA
-----------------------------------	------------------

Dimensions

Product Net Width	81 mm
Product Net Depth / Length	82.5 mm
Product Net Height	95 mm
Product Net Weight	735 g

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	86 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	770 g
Package Level 1 EAN	7612271214180

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CCC413009D0201
--------------------------------	-----------------

Environmental Information	2CCY413207D0203
Instructions and Manuals	2CCC413015M0403
RoHS Information	2CCC413009D0201 9AKK107680A3903

Popular Downloads

Data Sheet, Technical Information	2CCC413003C0208
Instructions and Manuals	2CCC413015M0403
Dimension Diagram	2CCC413003C0201

Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

