

PRODUCT-DETAILS

SAR/A1.0.1-24

SAR/A1.0.1-24 Room temperature controller control element ABB Tenton®



General Information

Extended Product Type	SAR/A1.0.1-24
Product ID	2CKA006134A0346
EAN	4011395252093
Catalog Description	SAR/A1.0.1-24 Room temperature controller control element ABB Tenton®
Long Description	The control element is used in conjunction with the FCC / S FanCoil controller or the VC / S valve controller for temperature control.

Ordering

EAN	4011395252093
Customs Tariff Number	90329000
Minimum Order Quantity	1 piece
E-Number (Sweden)	1739792

Dimensions

Product Net Depth / Length	0.015 m
Product Net Height	0.08 m
Product Net Width	0.08 m
Product Net Weight	92 g

Container Information

Package Level 1 Units	1 piece
Package Level 1 EAN	4011395252093
Package Level 1 Depth / Length	0.095 m
Package Level 1 Height	0.091 m
Package Level 1 Width	0.038 m
Package Level 1 Gross Weight	92 g
Package Level 2 Units	10 piece
Package Level 2 Depth / Length	0.298 m
Package Level 2 Height	0.112 m
Package Level 2 Width	0.168 m
Package Level 2 Gross Weight	920 g
Package Level 3 Units	1620 piece
Package Level 3 Depth / Length	1.2 m
Package Level 3 Height	1.158 m
Package Level 3 Width	0.8 m
Package Level 3 Gross Weight	170 kg

Certificates and Declarations (Document Number)

Instructions and Manuals	2CKA000173B9390
Declaration of Conformity - CE	DEBJE-2CKA006134A0346-ROHS
RoHS Information	9AKK104295D8727

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 6	EC001101 - Room temperature controller for bus system
ETIM 7	EC001101 - Room temperature controller for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Home and Building Automation → KNX → Heating, Ventilation and Air Conditioning → Thermostats

Low Voltage Products and Systems → Home and Building Automation → KNX → User Operation - ABB-Tenton® → 10 fold

Low Voltage Products and Systems → Home and Building Automation → KNX → User Operation - ABB-Tenton® → 6 fold

