

PRODUCT-DETAILS

6817/62-24-500

6817/62-24-500 Busch-Presence detector Compact, e-contact 8 metres



General Information	
Extended Product Type	6817/62-24-500
Product ID	2CKA006800A2737
EAN	4011395217580
Catalog Description	6817/62-24-500 Busch-Presence detector Compact, e-contact 8 metres
Long Description	Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With electronic switch contact for LED operation. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 6.5 m, walking persons: up to Ø 8 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With brightness-independent test mode for evaluating the detection zone. With teach-in function of the brightness switching threshold, IR service remote control required. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 48 sectors with 496 switching segments. Switch-off delay: approx. 1 min 30 min. or short-time pulse adjustable. Remote control possible via IR service remote control 6843. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

Ordering	
1301054	
4011395217580	
1 piece	
85365080	

Dimensions		
Product Net Width	0.094 m	
Product Net Height	0.094 m	
Product Net Depth / Length	0.059 m	
Product Net Weight	293 g	

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	293 g
Package Level 1 EAN	4011395217580

Environmental

RoHS Status

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information Auxiliary Voltage AC/DC 110 V AC/DC 230 V AC/DC Color studio white matt Connection Type Plug Clamp Current Range Maximum 350 A Degree of Protection IP40 Frequency (f) 50...60 Hz Illuminance 5...2000 lx Material Material quality: Thermoplastic Material: Plastic Mounting Type Flush-mounted Number of Outputs 1 Product Main Type Busch-Presence detector Compact, e-contact Product Name Busch-Presence detector Compact, e-contact 8 metres Product Range Movement detector Rated Voltage (Ur) 230 V 20150724 **RoHS** Date Surface Finishing Surface protection: Untreated Surface finishing: Matt

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	2CKA001473B9577
Declaration of Conformity - CE	2CKA100000E0692
RoHS Information	9AKK104295D8727

Classifications

ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems \rightarrow StandAlone Electronics \rightarrow Presence Detector \rightarrow Presence Detector Series \rightarrow IR Controlled Devices (Master) \rightarrow Presence Detector Compact, e Contact

