

PRODUCT-DETAILS

6819/31-24-500

6819/31-24-500 Busch-Presence detector Universal BT, relay 12 meters



General Information

Extended Product Type	6819/31-24-500
Product ID	2CKA006800A2741
EAN	4011395217634
Catalog Description	6819/31-24-500 Busch-Presence detector Universal BT, relay 12 meters

Long Description

Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With Bluetooth interface for parameterization and operation. Adjustment of all setting options via smartphone or tablet. Light control via smartphone or tablet app. With power relays for LED operation. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor). With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 72 sectors with 640 switching segments. Individual deactivation and adjustment of sensitivity of individual sensors possible. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. With selectable dynamic switch-off delay. Suitable for false ceilings with a board thickness from 9 to 25 mm.

Ordering

E-Number (Sweden)	1301057
EAN	4011395217634
Minimum Order Quantity	1 piece

Customs Tariff Number	85365080
-----------------------	----------

Dimensions

Product Net Width	0.094 m
Product Net Height	0.094 m
Product Net Depth / Length	0.072 m
Product Net Weight	306 g

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	306 g
Package Level 1 EAN	4011395217634

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Additional Information

Auxiliary Voltage AC/DC	110 V AC/DC 230 V AC/DC
Color	studio white matt
Connection Type	Plug Clamp
Current Range	Maximum 800 A
Degree of Protection	IP40
Frequency (f)	50...60 Hz
Illuminance	5...2000 lx
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush-mounted
Number of Outputs	1
Product Main Type	Busch-Presence detector Universal BT, relay
Product Name	Busch-Presence detector Universal BT, relay 12 meters
Product Range	Movement detector
Rated Voltage (U _r)	230 V
RoHS Date	20150724
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CKA001473B9577
Declaration of Conformity - CE	DEBJE-2CKA006800A2741-ROHS
RoHS Information	9AKK104295D8727

Classifications

ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → StandAlone Electronics → Presence Detector → Presence Detector Series → Bluetooth Controlled Devices (Master) → Presence Detector Universal BT, DALI

