

PRODUCT-DETAILS

6817/33-24-500

6817/33-24-500 Busch-Presence detector Universal BT, e-contact 12 meters



General Information	
Extended Product Type	6817/33-24-500
Product ID	2CKA006800A2743
EAN	4011395217658
Catalog Description	6817/33-24-500 Busch-Presence detector Universal BT, e-contact 12 meters
Long Description	Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With Bluetooth interface for parameterization and operation. Adjustment of all setting options via smartphone or tablet. Light control via smartphone or tablet app. With electronic switch contact for LED operation. With selectable soft ON/OFF function. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor). With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 72 sectors with 640 switching segments. Individual deactivation and adjustment of sensitivity of individual sensors possible. Switch-off delay: approx. 1 min 30 min. or short-time pulse adjustable. With selectable dynamic switch-off delay.

Ordering	
E-Number (Sweden)	1301058
EAN	4011395217658
Minimum Order Quantity	1 piece

Customs Tariff Number

85365080

Dimensions	
Product Net Width	0.094 m
Product Net Height	0.094 m
Product Net Depth / Length	0.059 m
Product Net Weight	289 g

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	290 g
Package Level 1 EAN	4011395217658

Environmental

RoHS Status

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Auxiliary Voltage AC/DC	110 V AC/DC
Auxiliary voltage AC/DC	230 V AC/DC
C-law	
Color	studio white matt
Connection Type	Plug Clamp
Current Range	Maximum 350 A
Degree of Protection	IP40
Frequency (f)	5060 Hz
Illuminance	52000 lx
Material	Material quality: Thermoplastic
	Material: Plastic
Mounting Type	Flush-mounted
Number of Outputs	1
Product Main Type	Busch-Presence detector Universal BT, e-contact
Product Name	Busch-Presence detector Universal BT, e-contact 12 meters
Product Range	Movement detector
Rated Voltage (U _r)	230 V
RoHS Date	20150724
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	2CKA001473B9577
Declaration of Conformity - CE	DEBJE-2CKA006800A2743-ROHS
RoHS Information	9AKK104295D8727

Classifications	
ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems \rightarrow StandAlone Electronics \rightarrow Presence Detector \rightarrow Presence Detector Series \rightarrow Bluetooth Controlled Devices (Master) \rightarrow Presence Detector Universal BT, e Contact

