

PRODUCT-DETAILS

6819/39-183-500

6819/39-183-500 Busch-Presence detector Universal, slave, DALI 12 meters



General Information

| | |
|-----------------------|---|
| Extended Product Type | 6819/39-183-500 |
| Product ID | 2CKA006800A2793 |
| EAN | 4011395218242 |
| Catalog Description | 6819/39-183-500 Busch-Presence detector Universal, slave, DALI 12 meters |
| Long Description | DALI slave presence detector for extension of the detection range of DALI master presence detectors. For the supply of operating voltage via the DALI master. Power consumption on the DALI bus: max. 10 mA, corresponds to approx. 5 DALI operating devices. The communication with the DALI master is carried out via the DALI interface. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Visible height 23 mm. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Surveillance density: 72 sectors with 640 switching segments. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. |

Ordering

| | |
|------------------------|---------------|
| EAN | 4011395218242 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |

Dimensions

| | |
|---------------------|---------|
| Product Net Width | 0.094 m |
| Product Net Height | 0.094 m |
| Product Net Depth / | 0.072 m |

Length

| | |
|--------------------|-------|
| Product Net Weight | 272 g |
|--------------------|-------|

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 0.141 m |
| Package Level 1 Height | 0.095 m |
| Package Level 1 Depth / Length | 0.165 m |
| Package Level 1 Gross Weight | 272 g |
| Package Level 1 EAN | 4011395218242 |

Environmental

| | |
|-------------|---|
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|-------------|---|

Additional Information

| | |
|---------------------------------|--|
| Auxiliary Voltage AC/DC | 9.5 V AC/DC 22.5 V AC/DC |
| Color | aluminium silver |
| Connection Type | Plug Clamp |
| Degree of Protection | IP40 |
| Material | Material quality: Thermoplastic Material: Plastic |
| Mounting Type | Flush-mounted |
| Product Main Type | Busch-Presence detector Universal, slave, DALI |
| Product Name | Busch-Presence detector Universal, slave, DALI 12 meters |
| Product Range | Movement detector |
| Rated Voltage (U _r) | 16 V |
| RoHS Date | 20150727 |
| Surface Finishing | Surface protection: Lacquered Surface finishing: Matt |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|----------------------------|
| Data Sheet, Technical Information | 2CKA001473B9577 |
| Declaration of Conformity - CE | DEBJE-2CKA006800A2793-ROHS |
| RoHS Information | 9AKK104295D8727 |

Classifications

| | |
|---------------|--|
| ETIM 5 | EC000133 - Movement sensor complete |
| ETIM 6 | EC000133 - Movement sensor complete |
| ETIM 7 | EC000133 - Movement sensor complete |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → StandAlone Electronics → Presence Detector → Presence Detector Series → Slave Devices → Presence Detector Universal, DALI Slave

