

0.094 m

0.094 m

PRODUCT-DETAILS

Product Net Width

**Product Net Height** 

### 6819/59-183-500

## 6819/59-183-500 Busch-Presence detector Corridor, slave, DALI 30 metres



General Information	
Extended Product Type	6819/59-183-500
Product ID	2CKA006800A2795
EAN	4011395218266
Catalog Description	6819/59-183-500 Busch-Presence detector Corridor, slave, DALI 30 metres
Long Description	DALI slave presence detector for extension of the detection range of DALI master presence detectors. For the supply of operating voltage via the DALI master. Power consumption on the DALI bus: max. 10 mA, corresponds to approx. 5 DALI operating devices. The communication with the DALI master is carried out via the DALI interface.  Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 24 m x 3 m, frontal/lengthways to the detector 14 m x 3 m.  Mounting height 27 mm. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Surveillance density: 92 sectors with 368 switching segments. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

# Ordering EAN 4011395218266 Minimum Order Quantity 1 piece Customs Tariff Number 85365080 Dimensions

Product Net Depth / Length	0.076 m
Product Net Weight	282 g

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	283 g
Package Level 1 EAN	4011395218266

#### **Environmental**

RoHS Status Following EU Directive 2002/95/EC August 18, 2005 and amendment

#### **Additional Information**

7.0.0	
Auxiliary Voltage AC/DC	9.5 V AC/DC
	22.5 V AC/DC
Color	aluminium silver
Connection Type	Plug Clamp
Degree of Protection	IP40
Frequency (f)	5060 Hz
Illuminance	52000 lx
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush-mounted
Product Main Type	Busch-Presence detector Corridor, slave, DALI
Product Name	Busch-Presence detector Corridor, slave, DALI 30 metres
Product Range	Movement detector
Rated Voltage (U <sub>r</sub> )	16 V
RoHS Date	20150727
Surface Finishing	Surface protection: Lacquered Surface finishing: Matt

#### **Certificates and Declarations (Document Number)**

Data Sheet, Technical Information	2CKA001473B9577
Declaration of Conformity - CE	DEBJE-2CKA006800A2795-ROHS
RoHS Information	9AKK104295D8727

#### Classifications

ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

6819/59-183-500

#### Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow StandAlone\ Electronics \rightarrow Presence\ Detector \rightarrow Presence\ Detector\ Series \rightarrow Slave\ Devices \rightarrow Presence\ Detector\ Corridor,\ DALI\ Slave$ 

