

PRODUCT-DETAILS

## 6819/50-24-500

### 6819/50-24-500 Busch-Presence detector Corridor, relay 24 meters



#### General Information

Extended Product Type	6819/50-24-500
Product ID	2CKA006800A2797
EAN	4011395231920
Catalog Description	6819/50-24-500 Busch-Presence detector Corridor, relay 24 meters

Long Description	<p>Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With power relays for LED operation. Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 24 m x 3 m, frontal/lengthways to the detector 14 m x 3 m. Extension of the detection range by means of master/slave combination. Mounting height 27 mm. For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With brightness-independent test mode for evaluating the detection zone. With teach-in function of the brightness switching threshold, IR service remote control required. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 92 sectors with 368 switching segments Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. Remote control possible via IR service remote control 6843. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.</p>
------------------	--

#### Ordering

E-Number (Sweden)	1301056
EAN	4011395231920
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

---

## Dimensions

---

Product Net Width	0.094 m
Product Net Height	0.094 m
Product Net Depth / Length	0.076 m
Product Net Weight	316 g

---



---

## Container Information

---

Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	316 g
Package Level 1 EAN	4011395231920

---



---

## Environmental

---

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

---



---

## Additional Information

---

Auxiliary Voltage AC/DC	110 V AC/DC 230 V AC/DC
Color	studio white matt
Connection Type	Plug Clamp
Current Range	Maximum 800 A
Degree of Protection	IP40
Frequency (f)	50...60 Hz
Illuminance	5...2000 lx
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush-mounted
Number of Outputs	1
Product Main Type	Busch-Presence detector Corridor, relay
Product Name	Busch-Presence detector Corridor, relay 24 meters
Product Range	Movement detector
Rated Voltage (U <sub>r</sub> )	230 V
RoHS Date	20160705
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

---



---

## Certificates and Declarations (Document Number)

---

Data Sheet, Technical Information	2CKA001473B9577
Declaration of Conformity - CE	2CKA100000E0716
RoHS Information	9AKK104295D8727

---



---

## Classifications

---

ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → StandAlone Electronics → Presence Detector → Presence Detector Series → IR Controlled Devices (Master) → Presence Detector Corridor, Relay

