

PRODUCT-DETAILS

# SSPL25/M25/M

## M25 M TYPE SPL25 STAINLESS STEEL



### General Information

Extended Product Type	SSPL25/M25/M
Product ID	7TBA296030R0380
EAN	5020963053443
Catalog Description	M25 M TYPE SPL25 STAINLESS STEEL
Long Description	Stainless Steel Straight Swivel Fitting with External Thread, Conduit Size 25 Millimeters, Thread Size M25

### Ordering

EAN	5020963053443
-----	---------------

### Dimensions

Product Net Weight	.47 lb 213.152 g
--------------------	---------------------

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth / Length	1 in 25 mm
--------------------------------	---------------

### Additional Information

Application	For Insertion into Threaded Entries or Knockout to Connect Conduit
Brand / Label	Adaptaflex
Cable Entry Position	M25 Thread
Color	Metallic
Material	Stainless Steel
Number of Batteries	0
Product Name	METAL FLEX CONDUIT
Product Type	Liquid Tight Non-Metallic Fitting
Size	NC 25mm
UPC	786210259420

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	7TKK001232
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SSPL25/M25/M

### Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

