

PRODUCT-DETAILS

PAFS13/BL/50M

STD WGT BLK NYL COND NC13 50M



General Information

Extended Product Type	PAFS13/BL/50M
Product ID	7TCA296000R2155
EAN	5020963000690
Catalog Description	STD WGT BLK NYL COND NC13 50M
Long Description	Standard Weight Conduit, Nominal Conduit Size 13mm, NW Conduit Size 10, Fine Conduit Pitch, Outside Diameter 13.0mm, Inside Diameter 9.6mm, Static Bend Radius 25mm, Reel Length 50 Meters, Polyamide (Nylon) 6, Black

Ordering

EAN	5020963000690
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	3.12 lb 1.415 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	17 in 432 mm

Package Level 1 Height	6 in 152 mm
Package Level 1 Depth / Length	17 in 432 mm
Package Level 2 Units	1 piece
Package Level 2 Width	17 in 432 mm
Package Level 2 Height	37 in 940 mm
Package Level 2 Depth / Length	17 in 432 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings & Machinery
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	9.6 mm
Material	Polyamide/Nylon 6
Nominal Size	13 mm
Number of Batteries	0
Outside Diameter	13.0 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit with Fine Pitch
Radius	25 mm
Special Functions	High Fatigue Life, Self Extinguishing, Halogen Free
UPC	786210258584

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PAFS13/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PAFS13/BL/50M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

