

PRODUCT-DETAILS

S16/50M

50M X S16 CONDUIT



General Information

Extended Product Type	S16/50M
Product ID	7TCA296010R0040
EAN	5020963001277
Catalog Description	50M X S16 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 16mm, Outside Diameter 16.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 50 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963001277
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	20.06 lb 9.098 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	13.0 mm
Material	Galvanized Steel
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	16.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	35 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210261430

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S16/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S16/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

