

PRODUCT-DETAILS

SP12/OR/25M

25M X SP12/ORANGE CONDUIT



General Information

Extended Product Type	SP12/OR/25M
Product ID	7TCA296020R0063
EAN	5020963005138
Catalog Description	25M X SP12/ORANGE CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 12mm, Outside Diameter 14.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Orange

Ordering

EAN	5020963005138
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	8.21 lb 3.723 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Orange
Flexibility	High
Inside Diameter	10.3 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	5/16 in
Number of Batteries	0
Outside Diameter	14.0 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	30 mm
UPC	786210259130

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP12/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP12/OR/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

