

PRODUCT-DETAILS

SP32/BL/15M

15M X SP32/BLACK CONDUIT



General Information

Extended Product Type	SP32/BL/15M
Product ID	7TCA296020R0225
EAN	5020963052651
Catalog Description	15M X SP32/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 32mm, Outside Diameter 34.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 15 Meters, PVC Jacket with Galvanised Steel Core, Black

Ordering

EAN	5020963052651
-----	---------------

Dimensions

Product Net Depth / Length	15 m
Product Net Weight	20.45 lb 9.274 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	28.1 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1 in
Number of Batteries	0
Outside Diameter	34.0 mm
Product Name	FLEX TUBING OF STEEL W/O FITTINGS
Product Type	High Flexibility Conduit
Radius	60 mm
UPC	786210296388

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP32/BL/15M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP32/BL/15M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

