

PRODUCT-DETAILS

SP40/BL/10M

10M X SP40/BLACK CONDUIT



General Information

Extended Product Type	SP40/BL/10M
Product ID	7TCA296020R0265
EAN	5020963000638
Catalog Description	10M X SP40/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 40mm, Outside Diameter 44.5mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 10 Meters, PVC Jacket with Galvanised Steel Core, Black

Ordering

EAN	5020963000638
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	20.86 lb 9.46 kg

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	2 piece

Package Level 2 Width	17 in 432 mm
Package Level 2 Height	16 in 406 mm
Package Level 2 Depth / Length	16 in 406 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	37.7 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	44.5 mm
Product Name	flex metal conduit
Product Type	High Flexibility Conduit
Radius	80 mm
UPC	786210249254

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP40/BL/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP40/BL/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

