

PRODUCT-DETAILS

# SPL63/PG48/M

## PG48 M TYPE



### General Information

Extended Product Type	SPL63/PG48/M
Product ID	7TCA296030R0325
EAN	5020963000799
Catalog Description	PG48 M TYPE
Long Description	Nickel Plated Brass Liquid Tight Straight Swivel Fitting with External Thread, Nominal Conduit Size 63 Millimeters, PG Thread Size PG48

### Ordering

EAN	5020963000799
-----	---------------

### Dimensions

Product Net Weight	1.17 lb 530.612 g
--------------------	----------------------

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /  
Length

1 in  
25 mm

## Additional Information

Application	For Insertion into Threaded Entries or Knockout to Connect Conduit
Brand / Label	Adaptaflex
Cable Entry Position	PG48 Thread
Color	Metallic
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Liquid Tight Non-Metallic Fitting
Size	2 Inch
Surface Finishing	Nickel Plated
UPC	786210275284

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK107492A2426
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL63/PG48/M

## Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

