

PRODUCT-DETAILS

SPLHC20/25M

25M X SPLHC20 CONDUIT



General Information

Extended Product Type	SPLHC20/25M
Product ID	7TCA296030R0340
EAN	5020963005824
Catalog Description	25M X SPLHC20 CONDUIT
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Ordering

EAN	5020963005824
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	22.47 lb 10.19 kg

Container Information

Package Level 2 Units	6 piece
Package Level 2 Width	37 in

	940 mm
Package Level 2 Height	17 in
	432 mm
Package Level 2 Depth / Length	17 in
	432 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	flexible metal conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	80 mm
UPC	786210245645

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC20/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

