

PRODUCT-DETAILS

# SPUL20/50M

## 50M X SPUL20/GREY CONDUIT



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | SPUL20/50M   |
| Product ID            | 7TCA296030R0367  |
| EAN                   | 5020963003851  |
| Catalog Description   | 50M X SPUL20/GREY CONDUIT  |
| Long Description      | Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 50 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Grey |

### Ordering

|     |               |
|-----|---------------|
| EAN | 5020963003851 |
|-----|---------------|

### Dimensions

|                            |                       |
|----------------------------|-----------------------|
| Product Net Depth / Length | 50 m                  |
| Product Net Weight         | 57.32 lb<br>25.995 kg |

### Container Information

|                       |         |
|-----------------------|---------|
| Package Level 2 Units | 1 piece |
| Package Level 2 Width | 1 in    |

|                                |       |
|--------------------------------|-------|
|                                | 25 mm |
| Package Level 2 Height         | 1 in  |
|                                | 25 mm |
| Package Level 2 Depth / Length | 1 in  |
|                                | 25 mm |

### Additional Information

|                     |   |
|---------------------|---|
| Application         | Flexible Protection Systems                             |
| Brand / Label       | Adaptaflex  |
| Color               | Gray  |
| Flexibility         | Medium  |
| Inside Diameter     | 15.9 mm   |
| Material            | Galvanized Steel Core with PVC Cover and Copper Packing |
| Nominal Size        | 1/2 in<br>NC20  |
| Number of Batteries | 0   |
| Outside Diameter    | 21.1 mm   |
| Product Name        | flexible metal conduit                                  |
| Product Type        | Liquid Tight, Medium Flexibility Conduit                |
| Radius              | 80 mm   |
| Special Functions   | High UV Protection                                      |
| Standards           | UL Listed, CSA  |
| UPC                 | 786210247564  |

### Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | SPUL20/50M      |
| Declaration of Conformity - CE    | 9AKK107492A9618 |
| Instructions and Manuals          | SPUL20/50M      |

### Classifications

|                                    |                                     |
|------------------------------------|-------------------------------------|
| ETIM 6                             | EC001179 - Protective metallic hose |
| ETIM 7                             | EC001179 - Protective metallic hose |
| UNSPSC                             | 39131706                            |
| WEEE Category                      | Product Not in WEEE Scope           |
| IDEA Granular Category Code (IGCC) | 5543 >> Liquid Tight Conduit        |

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

