

PRODUCT-DETAILS

SPUL32/25M

FLEX COND TO UL SPEC NC32 25M



General Information

Extended Product Type	SPUL32/25M
Product ID	7TCA296030R0370
EAN	5020963009037
Catalog Description	FLEX COND TO UL SPEC NC32 25M
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 165mm, Reel Length 25 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Grey

Ordering

EAN	5020963009037
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	36.37 lb 16.494 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Flexible Protection Systems
Brand / Label	Adaptaflex
Color	Gray
Flexibility	Medium
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with PVC Cover and Copper Packing
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	33.1 mm
Product Name	ADAPTAFLEX
Product Type	Liquid Tight, Medium Flexibility Conduit
Radius	165 mm
Special Functions	High UV Protection
Standards	UL Listed, CSA
UPC	786210275321

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPUL32/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPUL32/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

