

PRODUCT-DETAILS

SPUL20/BL/25M

SPUL20/BLACK CONDUIT X 25M



General Information

Extended Product Type	SPUL20/BL/25M
Product ID	7TCA296030R0425
EAN	5020963801167
Catalog Description	SPUL20/BLACK CONDUIT X 25M
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Black

Ordering

EAN	5020963801167
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	22.37 lb 10.145 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Flexible Protection Systems
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with PVC Cover and Copper Packing
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	FLEXIBLE CONDUIT
Product Type	Liquid Tight, Medium Flexibility Conduit
Radius	80 mm
Special Functions	High UV Protection
Standards	UL Listed, CSA
UPC	786210289960

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPUL20/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPUL20/BL/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

