

PRODUCT-DETAILS

SB16/25M

STEEL BRAIDED COND NC16 25M



Product image
not available

General Information

Extended Product Type	SB16/25M
Product ID	7TCA296040R0031
EAN	5020963004346
Catalog Description	STEEL BRAIDED COND NC16 25M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.5mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 25 Meters, Galvanised Steel Core and Overbraid

Ordering

EAN	5020963004346
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	42.9 lb 19.456 kg

Container Information

Package Level 2 Units	2 piece
Package Level 2 Width	37 in 940 mm

Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	13.0 mm
Material	Galvanized Steel Core and Overbraid
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	17.5 mm
Product Name	flex metal conduit
Product Type	Low Fire Hazard Conduit
Radius	35 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210244235

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SB16/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SB16/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available