

PRODUCT-DETAILS

SPB10/25M

STEEL PVC BRAID COND NC10 25M



General Information

Extended Product Type	SPB10/25M
Product ID	7TCA296040R0094
EAN	5020963008238
Catalog Description	STEEL PVC BRAID COND NC10 25M
Long Description	Highly Flexible Steel Conduit, Nominal Conduit Size 10mm, Outer Diameter 10mm, Inner Diameter 6.8mm, Maximum Bend Radius 25mm, Reel Length 25 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid

Ordering

EAN	5020963008238
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	6.67 lb 3.025 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Material	Galvanized Steel Core and Overbraid with PVC Jacket
Nominal Size	1/4 in 10 mm
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	25 mm
Special Functions	Very High UV Protection
UPC	786210274621

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPB10/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPB10/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

