

PRODUCT-DETAILS

XF25/30M

XTRA FLEX 25MM REELED



General Information

Extended Product Type	XF25/30M
Product ID	7TCA296060R0121
EAN	5020963001048
Catalog Description	XTRA FLEX 25MM REELED
Long Description	Standard Weight Conduit, Nominal Conduit Size 25mm, Outside Diameter 27.5mm, Inside Diameter 22.0mm, Static Bend Radius 50mm, Reel Length 30 Meters, PVCu Spiral with Plasticised PVC Covering, Black

Ordering

EAN	5020963001048
-----	---------------

Dimensions

Product Net Depth / Length	30 m
Product Net Weight	9.92 lb 4.499 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors, Torsional Equipment
Brand / Label	Adaptaflex
Color	Black
Flexibility	Very High
Inside Diameter	22.0 mm
Material	PVCu Spiral with Plasticised Covering
Nominal Size	25 mm
Number of Batteries	0
Outside Diameter	27.5 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit
Radius	50 mm
Special Functions	High UV Protection
UPC	786210253367

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	XF25/30M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	XF25/30M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

