

PRODUCT-DETAILS

# XF40/30M

## XTRA FLEX 40MM REELED



### General Information

Extended Product Type	XF40/30M
Product ID	7TCA296060R0140
EAN	5020963004612
Catalog Description	XTRA FLEX 40MM REELED
Long Description	Standard Weight Conduit, Nominal Conduit Size 40mm, Outside Diameter 44.0mm, Inside Diameter 38.0mm, Static Bend Radius 80mm, Reel Length 30 Meters, PVCu Spiral with Plasticised PVC Covering, Black

### Ordering

EAN	5020963004612
-----	---------------

### Dimensions

Product Net Depth / Length	30 m
Product Net Weight	18.52 lb 8.399 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Indoors / Outdoors, Torsional Equipment
Brand / Label	Adaptaflex
Color	Black
Flexibility	Very High
Inside Diameter	38.0 mm
Material	PVCu Spiral with Plasticised Covering
Nominal Size	40 mm
Number of Batteries	0
Outside Diameter	44.0 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit
Radius	80 mm
Special Functions	High UV Protection
UPC	786210259604

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	XF40/30M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	XF40/30M

## Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

