

PRODUCT-DETAILS

SPLB25/M25/A

NC25 LTADPTR SPLHC BRAID M25 FIXED



General Information

Extended Product Type	SPLB25/M25/A
Product ID	7TCA296100R0158
EAN	5020963007491
Catalog Description	NC25 LTADPTR SPLHC BRAID M25 FIXED
Long Description	Nickel Plated Brass Straight Fitting with Fixed External Thread, Nominal Conduit Size 25 Millimeters, IP68 Rating, Metric Thread Size M25

Ordering

EAN	5020963007491
-----	---------------

Dimensions

Product Net Weight	.53 lb 240.363 g
--------------------	---------------------

Container Information

Package Level 2 Units	10 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /
Length

1 in
25 mm

Additional Information

Application	For Insertion into Threaded Entries or Knockout to Connect Conduit
Brand / Label	Adaptaflex
Cable Entry Position	M25 Thread
Color	Metallic
Material	Brass
Number of Batteries	0
Product Name	brass fitting for conduit
Product Type	Conduit Fitting with Metric Threads
Size	3/4 Inch
Surface Finishing	Nickel Plated
UPC	786210245447

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLB25/M25/A
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLB25/M25/A

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

