

PRODUCT-DETAILS

SPLHCB40/10M

LQT BRD SPLHC40 10M REELS



General Information

Extended Product Type	SPLHCB40/10M
Product ID	7TCA296100R0174
EAN	5020963050275
Catalog Description	LQT BRD SPLHC40 10M REELS
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit with Stainless Steel Braid, Medium Flexibility, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 10 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Ordering

EAN	5020963050275
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	23.92 lb 10.848 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	35.4 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1-1/4 in NC40
Number of Batteries	0
Outside Diameter	41.8 mm
Product Name	flexible metal conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	180 mm
UPC	786210245553

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHCB40/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHCB40/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

