

PRODUCT-DETAILS

SPTC20/25M

SP20 TIN COPPER BRAIDED 25M



General Information

Extended Product Type	SPTC20/25M
Product ID	7TCA296100R0184
EAN	5020963010859
Catalog Description	SP20 TIN COPPER BRAIDED 25M
Long Description	Highly Flexible Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, Galvanised Steel Core with PVC Jacket and Tinned Copper Overbraid, Black

Ordering

EAN	5020963010859
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	16.53 lb 7.497 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	16.9 mm
Material	Galvanized Steel Core, Tinned Copper Overbraid with PVC Jacket
Nominal Size	1/2 in
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	45 mm
Special Functions	Very High UV Protection
UPC	786210247434

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPTC20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPTC20/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

