

PRODUCT-DETAILS

SPTC50/10M

SP T/C BR FLEX NC50 10M



General Information

Extended Product Type	SPTC50/10M
Product ID	7TCA296100R0188
EAN	5020963018138
Catalog Description	SP T/C BR FLEX NC50 10M
Long Description	Highly Flexible Conduit, Nominal Conduit Size 50mm, Outside Diameter 56.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Tinned Copper Overbraid, Black

Ordering

EAN	5020963018138
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	25.49 lb 11.56 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	48.4 mm
Material	Galvanized Steel Core, Tinned Copper Overbraid with PVC Jacket
Nominal Size	1-1/2 in
Number of Batteries	0
Outside Diameter	56.0 mm
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	90 mm
Special Functions	Very High UV Protection
UPC	786210247557

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPTC50/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPTC50/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

