

PRODUCT-DETAILS

# SSB25/25M

## S.STL BRD S.STL COND NC25 25M



### General Information

Extended Product Type	SSB25/25M
Product ID	7TCA296100R0193
EAN	5020963011375
Catalog Description	S.STL BRD S.STL COND NC25 25M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 25 Meters, 316 Stainless Steel Core and Overbraid

### Ordering

EAN	5020963011375
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	12.68 lb 5.751 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

### Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	21.4 mm
Material	Stainless Steel Core and Overbraid
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	55 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210260723

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SSB25/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SSB25/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

