

PRODUCT-DETAILS

SSBGS16/25M

SSTL BRD GALV COND25MREELS



Product image
not available

General Information

Extended Product Type	SSBGS16/25M
Product ID	7TCA296100R0196
EAN	5020963775321
Catalog Description	SSTL BRD GALV COND25MREELS
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.5mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 25 Meters, Galvanised 316 Stainless Steel Core and Overbraid

Ordering

EAN	5020963775321
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	10.03 lb 4.549 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	13.0 mm
Material	Galvanized Steel Core and Stainless Steel Overbraid
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	17.5 mm
Product Name	metal flex conduit
Product Type	Low Fire Hazard Conduit
Radius	35 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210260655

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SSBGS16/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SSBGS16/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available