

PRODUCT-DETAILS

SSBGS20/25M

S.STL BRD GALV COND NC20 25M



General Information

Extended Product Type	SSBGS20/25M
Product ID	7TCA296100R0197
EAN	5020963029066
Catalog Description	S.STL BRD GALV COND NC20 25M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, Galvanised 316 Stainless Steel Core and Overbraid

Ordering

EAN	5020963029066
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	13.01 lb 5.9 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	16.9 mm
Material	Galvanized Steel Core and Stainless Steel Overbraid
Nominal Size	1/2 in
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	45 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210260662

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SSBGS20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SSBGS20/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

