

PRODUCT-DETAILS

# SS10/50M

## 50M X SS10 CONDUIT



### General Information

Extended Product Type	SS10/50M
Product ID	7TCA296120R0006
EAN	5020963049446
Catalog Description	50M X SS10 CONDUIT
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 10mm, Outside Diameter 9.0mm, Inside Diameter 6.8mm, Static Bend Radius 25mm, Reel Length 50 Meters, 316 Stainless Steel, Corrosion Resistant

### Ordering

EAN	5020963049446
-----	---------------

### Dimensions

Product Net Depth / Length	50 m
Product Net Weight	10.68 lb 4.844 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	6.8 mm
Material	Stainless Steel
Nominal Size	1/4 in 10 mm
Number of Batteries	0
Outside Diameter	9.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	25 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210260754

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS10/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS10/50M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

