

PRODUCT-DETAILS

SS12/50M

50M X SS12 CONDUIT



General Information

Extended Product Type	SS12/50M
Product ID	7TCA296120R0010
EAN	5020963048876
Catalog Description	50M X SS12 CONDUIT
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 12mm, Outside Diameter 13.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 50 Meters, 316 Stainless Steel, Corrosion Resistant

Ordering

EAN	5020963048876
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	11.57 lb 5.247 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	10.3 mm
Material	Stainless Steel
Nominal Size	5/16 in
Number of Batteries	0
Outside Diameter	13.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	30 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210260761

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS12/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS12/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

