

PRODUCT-DETAILS

SS16/10M

NC16 SS CONDUIT NW-16 LEN 10 METER



General Information

Extended Product Type	SS16/10M
Product ID	7TCA296120R0011
EAN	5020963026546
Catalog Description	NC16 SS CONDUIT NW-16 LEN 10 METER
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 16mm, Outside Diameter 16.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 10 Meters, 316 Stainless Steel, Corrosion Resistant

Ordering

EAN	5020963026546
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	3.44 lb 1.56 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	13.0 mm
Material	Stainless Steel
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	16.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	35 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210260778

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS16/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS16/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

