

PRODUCT-DETAILS

SS25/25M

25M X SS25 CONDUIT



General Information

Extended Product Type	SS25/25M
Product ID	7TCA296120R0026
EAN	5020963008900
Catalog Description	25M X SS25 CONDUIT
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 25mm, Outside Diameter 25.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant

Ordering

EAN	5020963008900
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	13.86 lb 6.286 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	9.5 in 241 mm

Package Level 1 Height	25 in 635 mm
Package Level 1 Depth / Length	25 in 635 mm
Package Level 2 Units	1 piece
Package Level 2 Width	9.5 in 241 mm
Package Level 2 Height	25 in 635 mm
Package Level 2 Depth / Length	25 in 635 mm
Package Level 3 Units	10 piece
Package Level 3 Width	210 in 5334 mm
Package Level 3 Height	210 in 5334 mm
Package Level 3 Depth / Length	410 in 10414 mm

Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	21.4 mm
Material	Stainless Steel
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	25.0 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	55 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210249568

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS25/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS25/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

