

PRODUCT-DETAILS

SS16/50M

SS16 CONDUIT 50M REELS



Product image
not available

General Information

Extended Product Type	SS16/50M
Product ID	7TCA296120R0040
EAN	5020963801266
Catalog Description	SS16 CONDUIT 50M REELS
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 16mm, Outside Diameter 16.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 50 Meters, 316 Stainless Steel, Corrosion Resistant

Ordering

EAN	5020963801266
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	17.2 lb 7.8 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	16 in 406 mm

Package Level 2 Height	5.5 in 140 mm
Package Level 2 Depth / Length	16 in 406 mm

Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	13.0 mm
Material	Stainless Steel
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	16.0 mm
Product Name	FLEXIBLE METAL CONDUIT
Product Type	Low Fire Hazard Conduit
Radius	35 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210289199

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS16/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS16/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available