

PRODUCT-DETAILS

# FLH0620

## LT-H FLEXIBLE CONDUIT 32MM



### General Information

Extended Product Type	FLH0620
Product ID	7TCA297020R0149
EAN	5011949202993
Catalog Description	LT-H FLEXIBLE CONDUIT 32MM
Long Description	Liquid Tight, High Temperature Conduit, Nominal Conduit Size 32mm, 1 Inch US Trade Size, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 20 Meters, Galvanised Steel Core, String Packing with Thermoplastic Rubber Covering, Black

### Ordering

EAN	5011949202993
-----	---------------

### Dimensions

Product Net Depth / Length	20 m
Product Net Weight	28.39 lb 12.875 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Extreme Temperature Environments
Brand / Label	Kopex
Color	Black
Flexibility	High
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with String Packing and Thermoplastic Rubber Coating
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	33.1 mm
Product Name	flex metal conduit
Product Type	Liquid Tight High Temperature Conduit
Radius	145 mm
Standards	BSI Kitemark KM-90009, Low Voltage Directive
UPC	786210276663

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	FLH0620
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	FLH0620

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

