

PRODUCT-DETAILS

# FLT0620

## LT-T FLEXIBLE CONDUIT 32MM



### General Information

Extended Product Type	FLT0620
Product ID	7TCA297020R0186
EAN	5011949214897
Catalog Description	LT-T FLEXIBLE CONDUIT 32MM
Long Description	Liquid Tight, Low Fire Hazard Conduit, Nominal Conduit Size 32mm, 1 Inch US Trade Size, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 20 Meters, Galvanised Steel Core, String Packing with LFH Covering, Black

### Ordering

EAN	5011949214897
-----	---------------

### Dimensions

Product Net Depth / Length	20 m
Product Net Weight	36.82 lb 16.698 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

**Additional Information**

Application	Indoors / Outdoors, Marine, Buildings, & Rail Infrastructure Where Low Smoke and Toxicity are of Concern
Brand / Label	Kopex
Color	Black
Flexibility	Medium
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with String Packing and Low Fire Hazard Coating
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	33.1 mm
Product Name	FLEXIBLE CONDUIT
Product Type	Liquid Tight Low Fire Hazard Conduit
Radius	145 mm
Standards	BSI Kitemark KM-90009, Low Voltage Directive, London Underground I-085, NFF16-101 (I1 F1)
UPC	786210241418

**Certificates and Declarations (Document Number)**

Data Sheet, Technical Information	FLT0620
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	FLT0620

**Classifications**

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

**Categories**

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

