

PRODUCT-DETAILS

FSH0410

LT-H FLEXIBLE S/S CONDUIT 20MM 10M



General Information

Extended Product Type	FSH0410
Product ID	7TCA297070R0012
EAN	5011949218659
Catalog Description	LT-H FLEXIBLE S/S CONDUIT 20MM 10M
Long Description	Liquid Tight, High Temperature Conduit, Nominal Conduit Size 20mm, 1/2 Inch US Trade Size, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 10 Meters, IP66, IP67 Ratings, Stainless Steel AISI 316L Core, String Packing with Thermoplastic Rubber Covering, Black

Ordering

EAN	5011949218659
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	7.68 lb 3.483 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Extreme Temperature Environments
Brand / Label	Kopex
Color	Black
Flexibility	High
Inside Diameter	15.9 mm
Material	316 Stainless Steel Core with String Packing and Thermoplastic Rubber Coating
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	flex metal conduit
Product Type	Liquid Tight High Temperature Conduit
Radius	80 mm
Standards	BSI Kitemark KM-90009, Low Voltage Directive
UPC	786210276854

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	FSH0410
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	FSH0410

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

