

PRODUCT-DETAILS

FSH0430

LT-H FLEXIBLE S/STEEL CONDUIT 20MM



General Information

Extended Product Type	FSH0430
Product ID	7TCA297070R0013
EAN	5011949218666
Catalog Description	LT-H FLEXIBLE S/STEEL CONDUIT 20MM
Long Description	Liquid Tight, High Temperature Conduit, Nominal Conduit Size 20mm, 1/2 Inch US Trade Size, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 30 Meters, IP66, IP67 Ratings, Stainless Steel AISI 316L Core, String Packing with Thermoplastic Rubber Covering, Black

Ordering

EAN	5011949218666
-----	---------------

Dimensions

Product Net Depth / Length	30 m
Product Net Weight	23.05 lb 10.454 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Extreme Temperature Environments
Brand / Label	Kopex
Color	Black
Flexibility	High
Inside Diameter	15.9 mm
Material	316 Stainless Steel Core with String Packing and Thermoplastic Rubber Coating
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	flex metal conduit
Product Type	Liquid Tight High Temperature Conduit
Radius	80 mm
Standards	BSI Kitemark KM-90009, Low Voltage Directive
UPC	786210276861

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	FSH0430
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	FSH0430

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

