

PRODUCT-DETAILS

NC20/50M STND WEIGHT NYL COND NC20 50M BLK



General Information	
Extended Product Type	NC20/50N
Product ID	7TCA298000R023
EAN	502096302305
Catalog Description	STND WEIGHT NYL COND NC20 50M BL
Long Description	Standard Weight, General Purpose Conduit, NC Size 20/NW Size 17, Outside Diamete 21.2mm, Inside Diameter 16.6mm, Static Bend Radius 35mm, High Flexibility and Fatigue Life, IP40 Rating, Polyamide 6, Reel Length 50 Meters, Blac
Ordering	
Ordering	
EAN	502096302305
Dimensions	
Dimensions Product Net Depth / Length	50 n
Product Net Depth /	50 n 6.19 ll

Package Level 1 Units	1 piece
Package Level 1 Width	24.5 in
	622 mm

Package Level 1 Height	50 in
	1270 mm
Package Level 1 Depth /	24.5 in
Length	622 mm
Package Level 2 Units	1 piece
Package Level 2 Width	40 in
	1016 mm
Package Level 2 Height	50 in
	1270 mm
Package Level 2 Depth /	48 in
Length	1219 mm
Package Level 3 Units	1 piece
Package Level 3 Width	40 in
	1016 mm
Package Level 3 Height	50 in
	1270 mm
Package Level 3 Depth /	48 in
Length	1219 mm

Additional Information		
Application	Extensively Used in Harnesses on HGV and off Road Vehicles Applications Where Superior Protection Against Impact and Mechanical Shock is Preferred. The Conduit is Used for Both Chassis and Engine Applications and Can Be Used in a Wide Range of Temperatures	
Brand / Label	Harnessflex	
Color	Black	
Flexibility	Very High	
Inside Diameter	16.6 mm	
Material	Polyamide/Nylon 6	
Nominal Size	NC20/NW17	
Number of Batteries	0	
Outside Diameter	21.2 mm	
Product Name	"flexible conduit, nylon"	
Product Type	Standard Weight Conduit	
Radius	Static: 35 mm	
Standards	ADR Approved, RoHS, Conforms with End of Life Vehicle Directive (ELV) EU200/53/EC	
UPC	786210146928	

Data Sheet, Technical Information	NC20/50M
Declaration of Conformity - CE	9AKK107492A9616
Instructions and Manuals	NC20/50M
Classifications	
ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706

ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5540 >> Flexible Non-Metallic Conduit

Categories

Low Voltage Products and Systems \rightarrow Installation Products \rightarrow Cable Protection, Explosion Proof and Lighting \rightarrow Flexible Cable Protection Systems

