

PRODUCT-DETAILS

# BCG-M122

## NP BRASS CG M12X1.5 3-6.5MM



### General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | BCG-M122  |
| Product ID            | 7TCA303030R0003   |
| EAN                   | 5415022427431   |
| Catalog Description   | NP BRASS CG M12X1.5 3-6.5MM   |
| Long Description      | Non Armoured Cable Gland, Thread Size M12, Cable Range 3 to 6.5mm, Thread Length 6mm, Nickel Plated Brass |

### Ordering

|     |               |
|-----|---------------|
| EAN | 5415022427431 |
|-----|---------------|

### Dimensions

|                    |                    |
|--------------------|--------------------|
| Product Net Weight | .03 lb<br>13.605 g |
|--------------------|--------------------|

### Container Information

|                        |                  |
|------------------------|------------------|
| Package Level 1 Units  | 10 piece         |
| Package Level 1 Width  | 3.54 in<br>90 mm |
| Package Level 1 Height | 3.54 in<br>90 mm |

|                                |                    |
|--------------------------------|--------------------|
| Package Level 1 Depth / Length | 7.09 in<br>180 mm  |
| Package Level 2 Units          | 100 piece          |
| Package Level 2 Width          | 15.75 in<br>400 mm |
| Package Level 2 Height         | 11.02 in<br>280 mm |
| Package Level 2 Depth / Length | 3.94 in<br>100 mm  |

### Additional Information

|                     |   |
|---------------------|---|
| Application         | General purpose, Panel building, Light fixture and housings |
| Brand / Label       | ABB   |
| Color               | Metallic  |
| Material            | Brass   |
| Number of Batteries | 0   |
| Product Name        | NICKEL PLATED BRASS CABLE GLAND                             |
| Product Type        | Non Armoured Cable Gland                                    |
| Size                | M12   |
| Standards           | cULus, RoHS, WEEE, LVD                                      |
| Surface Finishing   | Nickel plated   |
| Temperature Range   | -20 to +100 °C  |
| UPC                 | 786210156354  |

### Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | TDS000028       |
| Declaration of Conformity - CE    | 9AKK107492A9845 |
| Instructions and Manuals          | BCG-M122        |

### Classifications

|                                    |                               |
|------------------------------------|-------------------------------|
| ETIM 6                             | EC000441 - Cable screw gland  |
| ETIM 7                             | EC000441 - Cable gland        |
| UNSPSC                             | 39121431                      |
| WEEE Category                      | Product Not in WEEE Scope     |
| IDEA Granular Category Code (IGCC) | 4601 >> Cable gland connector |

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

