

PRODUCT-DETAILS

422010

BSL+ 48...230/60L



General Information

Extended Product Type	422010
Product ID	7TCA304050R0021
EAN	5415022505955
Catalog Description	BSL+ 48...230/60L
Long Description	BSL+ 48...230/60L

Ordering

EAN	5415022505955
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	150 mm
Product Net Height	21 mm
Product Net Length	40 mm
Product Net Weight	2.8 lb 1.27 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Ambient Temperature	IEC62722-2-1 -30 ... 40 °C
Ballast Type	Current Controlled
Degree of Protection	IP68
Function	Escape route lighting
Housing Color	Stainless Steel
Housing Material	Stainless steel
Illuminance	45 lm Standby Mode 45 lm
Input Voltage Type	AC/DC
Lamp Type	LED not exchangeable
Number of Batteries	0
Outside Diameter	150 mm
	0,7 W
Product Main Type	SLAVE LUMINAIRE
Product Name	BSL+ 48...230/60L
Protection Class	Isolated
Rated Voltage (U _r)	48 ... 220 V
Type of Indicator	4-sided
UPC	075114403931

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK107492A8129
Declaration of Conformity - CE	9AKK107492A8365
Instructions and Manuals	422010

Classifications

ETIM 6	EC001957 - Emergency luminaire
ETIM 7	EC001957 - Emergency luminaire

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Emergency Lighting

