

SylFast T8

SylFast T8 1x18W EB (Electronic Ballast)

0046100



Range Features









PRODUCT OVERVIEW

Certifications	CE
Colour	White
Dimmable	No
EAN code	5410288461007
Housing	Sheet steel
IK rating	IK02
IP rating	IP20
Mount	Surface mounted
Ordering number	0046100
Technology	Fluorescent
Voltage (V)	220-240
Compatibile with bulbs of energy class:	A++ A+ A

DATA TABLE

General data	
Certifications	CE
Control gear availability	Included
Control gear mounting	Integral
Control gear type	Electronic
Dimmable	No
EAN code	5410288461007
Environment	Internal
Fixture rating	Open
General application	Logistics and Industry
Housing	Sheet steel
Mount	Surface mounted
National safety marks	CE
Ordering number	0046100
Product name	SylFast T8 1x18W EB (Electronic Ballast)



SylFast T8

SylFast T8 1x18W EB (Electronic Ballast)

0046100

Technology	Fluorescent
Compatibile with bulbs of energy class:	A++ A+ A
Product features	T8 fluorescent batten made from roll-formed steel. With punch out conduit holes on both ends and 3 pole terminal block. White body. For use with T8 lamps (ordered seperately). IP20. IK02. 220-240V. Class 1. Electronic ballast (non-dimmable).

Physical data

Colour	White
Height (mm)	74
IK rating	IK02
IP rating	IP20
Lamp included	No
Length (mm)	617
Weight (kg)	1.358
Width (mm)	51


Optical data

Distribution type	Direct (symmetric)	
Distribution type	Direct (Symmetric)	

Electrical data

Electrical protection	Class I
Glow wire test	850
Ta rating (°C)	-25 to +60
Voltage (V)	220-240

PHOTOMETRY



TECHNICAL DRAWINGS





SylFast T8 SylFast T8 1x18W EB (Electronic Ballast) 0046100

