

PAR 56 12V LED Swimming Pool

PAR 56 LED Receiver

0060523



Caractéristiques de la gamme

- Choice between RGB or fixed white version
- High power LED retrofit for incandescent PAR lamps
- Produces full spectrum of rich colours or white (multi colours)
- Sylvania patent pending colour control technology
- Simple on/off switching sets colour changing or fixed mode (can be achieved by using a standard switch)
- Optional Sylvania remote control and receiver available
- Identical shape to incandescent PAR56 = easy retrofit
- Unique sealing method guarantees IP68 water-tightness
- Die cast aluminium housing cools LEDs for high output
- Chlorine-resistant materials permits use in swimming pools
- Long lamp lifetime > 25.000 hours
- Low heat generation
- Applications
- All retrofit PAR56 underwater
- Swimming Pools
- Fountains
- Directions for use
- Only for use with magnetic (no electronic) transformer
- For adequate cooling, lamp must be operated under water



APERÇU DU PRODUIT

| | |
|---------------------|---------------|
| Technologie | LED |
| Numéro de commande | 0060523 |
| Type | LED |
| Code EAN | 5410288605234 |
| Watts (nominal) (W) | max. 250 |

PAR 56 12V LED Swimming Pool

PAR 56 LED Receiver

0060523

TABLE DE DONNÉES

Données générales

| | |
|-------------------------------|---|
| Technologie | LED |
| Numéro de commande | 0060523 |
| Type | LED |
| Code EAN | 5410288605234 |
| Longue description | Choice between RGB or fixed white version. High power LED retrofit for incandescent PAR lamps. Produces full spectrum of rich colours or white (multi colours). Sylvania patent pending colour control technology. Simple on/off switching sets colour changing or fixed mode (can be achieved by using a standard switch). Optional Sylvania remote control and receiver available. Identical shape to incandescent PAR56 = easy retrofit. Unique sealing method guarantees IP68 water-tightness. Die cast aluminium housing cools LEDs for high output. Chlorine-resistant materials permits use in swimming pools. Long lamp lifetime > 25.000 hours. Low heat generation. Applications. All retrofit PAR56 underwater. Swimming Pools. Fountains. Directions for use. Only for use with magnetic (no electronic) transformer. For adequate cooling, lamp must be operated under water |
| Nom du produit | PAR 56 LED Receiver |
| Quantité par emballage | 1 |

Données électriques

| | |
|----------------------------|----------|
| Watts (nominal) (W) | max. 250 |
|----------------------------|----------|

Données physiques

| | |
|---|-----------------------|
| Poids (kg) | 0.10 |
| Description de l'emballage | Box/Sleeve |
| Single package dimensions (L x W x H) (cm) | 17.00 x 9.00 x 4.50 |
| Outer package dimensions (L x W x H) (cm) | 34.00 x 30.00 x 35.00 |