



Main

Range of product	Odace
Product or component type	Battery powered push-button
Device presentation	Complete product
Type of packing	Box with eurohole

Complementary

Device mounting	Surface
Switch application	Lighting
Communication network type	Bluetooth low energy (BLE)
Transmission frequency	2.4 GHz
Operating distance	<= 15 m indoor use <= 30 m outdoor use
Fixing mode	By screws Double-sided adhesive tape
Provided equipment	Smart LED Cover plate
Colour tint	White (RAL 9003) cover plate
Number of batteries	1 CR2032 lithium battery - 3 V 2...5 years
Bulb type	LED E27 white 9 W 20000 h 220...240 V
Electrical durability	20000 cycles
Material	PBT (polybutylene terephthalate) GF30 support frame Thermoplastic ABS-UV stabilised centre plate
Height	71 mm
Width	71 mm
Depth	14 mm
Embedding depth	0 mm
Product weight	0.293 kg

Environment

Ambient air temperature for storage	-5...50 °C
Ambient air temperature for operation	5...35 °C
Relative humidity	20...95 %

Standards	EN 300-328 v1.8.1, 2012 EN 301-489-1 v1.9.2, 2011-09 EN 301-489-3 v1.6.1, 2013-06 EN 60950-1 2006
Directives	2014/30/EU - electromagnetic compatibility 2014/53/EU - radio equipment directive 2011/65/EU - RoHS directive
IK degree of protection	IK02
IP degree of protection	IP20
Environmental characteristic	Alcohol UV resistant Liquid soap Acetone Ammonia Oil Bleach Window-cleaning fluid Petrol
Environmental health and issues	Halogen free