


MP-11/11

Insulating mat class 0 – width 1 m

Series: MP-... 0_100



Application :

- Insulating mat for live and dead work. Maximum operating voltage: 1000 V AC - 1500 V DC.
- Used to cover the floor for the electrical protection of operators in electrical installations.
- Protect the workers from the ground potential.
- Must be adapted to the nominal voltage of the network supplying the installation on which it is used.

Features :

- In accordance with IEC 61111: 2009 standard and to specific properties of the "C" Category (extremely low temperature folding test at - 40 °C).
- RoHS2 compliant. REACH compliant (SVHC free).
- Material : elastomere without halogen.
- Unit test in production.
- D bar code (Datamatrix) on marking with direct link to user guide and technical sheet.
- Storage temperature: +10°C to +21°C.
- Operating temperature: -40°C to +55°C.

Description

Use	Indoor/Outdoor
Use	Indoor/Outdoor
Dimensions	
Thickness	2,2
Width	1 000
Fonctionnalité	
Weight	3
Material	Elastomère
Longueur	
Length	1 000
Tension	
Operating Voltage AC	1 000 V
Operating Voltage DC	1 500 V
Température	
Storage Temperature	+ 10°C/+ 21° C.
Operating Temperature	- 40°C/+ 55°