


MP-100/02-10

Insulating mat class 0 – width 1 m

Series: MP-... 0_100



Application :

- Insulating mat for live and dead work. Maximum operating voltage: 1000 V AC - 1500 V DC.
- Used to cover the floor for the electrical protection of operators in electrical installations.
- Protect the workers from the ground potential.
- Must be adapted to the nominal voltage of the network supplying the installation on which it is used.

Features :

- In accordance with IEC 61111: 2009 standard and to specific properties of the "C" Category (extremely low temperature folding test at - 40 °C).
- RoHS2 compliant. REACH compliant (SVHC free).
- Material : elastomere without halogen.
- Unit test in production.
- D bar code (Datamatrix) on marking with direct link to user guide and technical sheet.
- Storage temperature: +10°C to +21°C.
- Operating temperature: -40°C to +55°C.

Description

| | |
|-----------------------|-----------------|
| Use | Indoor/Outdoor |
| Color | Array |
| Use | Indoor/Outdoor |
| Dimensions | |
| Thickness | 2,2 |
| Width | 1 000 |
| Fonctionnalité | |
| Weight | 30 |
| Material | Elastomère |
| Longueur | |
| Length | 10 000 |
| Tension | |
| Operating Voltage AC | 1 000 V |
| Operating Voltage DC | 1 500 V |
| Température | |
| Storage Temperature | + 10°C/+ 21° C. |
| Operating Temperature | - 40°C/+ 55° |